



MOM 04

PRODUCT: FIBO WALL PANEL

DECOR:.....

PURCHASE DATE AND NUMBER:.....

SEALANT USED:.....

FORMAT: 0 13/32" x 18" x 11 5/8" with Aqualock click joint on 18" sides.

Product description

Fibo Kitchen Boards are based on a 7-layer exterior grade plywood core. The front is covered with a high pressure laminate with thickness 1/32"-3/64", while the backside is covered with a balance layer of thickness 1/64".

The panels have an average density of 790 kg/m³, thickness is 13/32" and have an Aqualock click. Width is 11 5/8". Standard length is 18", but decors are also available in 94 1/2".

Behind sink, hob(stove) and where Kitchen Board are exposed to water spillage or steam, use at all time sealant in click e.g. Fibo Seal.

Please note where the temperature is above 80°C/176°F eg. behind some gas stoves and cooktops, we recommend using a heat resistant decorative material(stainless steel is commonly used) or tempered glass product to protect the panel and avoid heat possibly dulling the panel. Please check with the manufacturer of gas appliance to determine required wall clearance for gas appliance installation to ensure temperatures don't exceed the level listed above where FIBO Kitchen Board is installed. Freestanding Ranges with a rear vertical control panel/display do not apply to this concern.

Cleaning Kitchen Board

For daily cleaning use pH neutral products, pH 7-9 and lukewarm water.

This applies to both panels, profiles and sealant. Do not allow bleach, abrasive cleaners, paint stripper, white spirit or toilet cleaner to come into contact with the panels. If chlorinated products are used, rins of with lukewarm water after max. 30 minutes as prolonged exposure to chlorine may stain some of the decors.

A newley installed Fibo Kitchen Wall, might have residues of a film from Fibo Wipes, this is a layer which should be removed with milde soap water within the first two weeks after installation so it does not set.

Methylated spirit can be used on stubborn stains or melamine sponge togheter with dishwasher soap. For cleaning of decors with deep structures we recommend lint free cloth, this applies for Cement (C) and Gemstone (GEM).

Warranty

See fibosystemusa.com, fibosystemcanada.com or contact info@fibosystem.com for warranty information.

Manufacturer

Address

Fibo AS

Industriveien 2, 4580 Lyngdal

+47 38 34 33 00

<http://www.fibosystem.com>

info@fibosystem.com

Elise Almås

02.03.2022

Phone

Web

E.mail

Contact Person

Publish Date