



MOM 02

PRODUCT: FIBO ALUMINIUM PROFILES FOR WALL PANELS AND KITCHEN BOARD

LENGTH: 580 mm, 2400 mm and 3000 mm

PURCHASE DATE AND NUMBER:.....

SEALANT USED (IF WET AREA):.....

Area of use For installation of Fibo Wall Panels in dry and wet areas and for Kitchen Board on kitchen walls.

Installation On solid wood studs or concrete/brick wall. Screwed to back wall.

Variants
Internal Corner Profile 90 degrees
2 -part internal corner profile 90 degrees
Internal Corner Profile 135 degrees
Hidden Internal Corner Profile 90 degrees
External Corner Profile 90 degrees
Stacking Profile
External Corner Profile 135 degrees
L-Profile Wide
L-Profile Small
Combi Profile
Base Profile
Base Profile - for flange

Screws Fibo Screws 3,0 x 20-35mm

Sealant Always use ETAG 022 approved sealants together with Fibo Wall Panels and Aluminium profiles in wet areas, e.g. Fibo Seal.

Product Description Fibo Aluminium profiles for Fibo Wall Panels and Fibo Kitchen Board

Surface treatment Anodized

Length 580 mm/2400 mm/3000 mm

Cleaning & Maintenance Uncured sealant residues are removed with Fibo Clean and Wipes. Wash with mild soap water. pH 4-9. White laquered profiles can also withstand cleaning with pH 10.

Notes:

Cutting Cut with a fine-tipped saw/possibly carbide blade.

Approvals:

SINTEF Technical Approval	SINTEF TG2289
European Technical Assesment (ETA)/CE	ETA 17-0124
MK Denmark	MK Approval no. 7.32/1462
VTT Certificate/Eurofins	VTT-C-2753-08

Manufacturer

Address	Fibo AS
Phone	Industriveien 2, 4580 Lyngdal
Fax	+47 38 34 33 00
Web	Not relevant
E.mail	http://www.fibosystem.com
Contact Person	ordre@fibosystem.com
	Elise Almås

Date: 30.07.2020