



MOM 04

PRODUCT: FIBO WALL PANEL

DECOR:.....

PURCHASE DATE AND NUMBER:.....

SEALANT USED:.....

FORMAT: 10,2x580x600 mm with Aqualock

Product description

Fibo Kitchen Boards are based on a 7-layer exterior grade plywood core. The front is covered with a high pressure laminate with thickness 0,6-0,9 mm, while the backside is covered with a balance layer of thickness 0,24-0,4 mm.

The panels have an average density of 790 kg/m³, thickness is 10,2 mm ± 0,4 mm and have an Aqualock click. Width is 600 mm. Width including the Aqualock click is 620 mm. The short ends have a straight cut and standard length is 580 mm, but decors are also available in 2400

Behind sink, hob(stove) and where Kitchen Board are exposed to water spillage or steam, use at all time sealant in click e.g. Fibo Seal.

In areas where the temperature is above 80°C/176°F eg. behind a hob, we recommend using a heat resistant sheet to protect the panel and avoid heat possibly dulling the panel surface. We do not recommend using Fibo panels alnoe behind a gas hob. Higher temperatures than 80°C/176°F might affect color and gloss levels of decors.

Cleaning Kitchen Board

For daily cleaning use pH neutral products, pH 7-9 and lukewarm water. This applies to both panels, profiles and sealant. Do not allow bleach, abrasive cleaners, paint stripper, white spirit or toilet cleaner to come into contact with the panels. If chlorinated products are used, rins of with lukewarm water after max. 30 minutes as prolonged exposure to chlorine may stain some of the decors.

A newley installed Fibo Kitchen Wall, might have residues of a film from Fibo Wipes, this is a layer which should be removed with milde soap water within the first two weeks after installation so it does not set.

Methylated spirit can be used on stubborn stains or melamine sponge togheter with dishwasher soap. For cleaning of decors with deep structures we recommend lint free cloth, this applies for Cement (C) and Gemstone (GEM).

Warranty

See fibosystem.com or contact info@fibosystem.com for warranty information.

Manufacturer

Address
Phone
Web
E.mail
Contact Person

Fibo AS
Industriveien 2, 4580 Lyngdal
+47 38 34 33 00
<http://www.fibosystem.com>
info@fibosystem.com
Elise Almås

Date: 30.07.2020