

# Management, Operations and Maintenance (MOM) Vito Lacquered Veneer

## FORMAT

TABLE 1: PRODUCT DIMENSIONS

PRODUCT	DIMENSION
Vito Lacquered Oak	2400 mm x 600 mm x 10 mm
	2720 mm x 600 mm x 10 mm
Vito Lacquered Birch	2400 mm x 600 mm x 10 mm
	2720 mm x 600 mm x 10 mm

## PRODUCT DESCRIPTION

Vito Lacquered Veneer consists of 7 layers of birch veneer with an 8th décor layer of lacquered birch or oak veneer. Backside is a thin paper balancing layer to maintain a flat and strong wall panel.

## INTENDED USE

Lacquered Veneer is a high-quality construction material for indoor use, in dry areas. It is ideal for walls where a seamless expression of natural wooding is required.

The panels have a hidden fastening system with a special click lock patent, which makes it easy to install and gives it a flawless appearance.

Vito Lacquered Veneer is a 10 mm thick panel delivered in a standard length of 2400 or 2720 mm by 600 mm width. The panels are installed with screws towards preferred backwall solution. We recommend use of Fibo Screws (article nr 810006/810007/810011) to maintain a guaranteed fit in the invisible lock-system.

TABLE 2: RELEVANT PROPERTIES

PROPERTIES	PERFORMANCE	HARMONIZED PRODUCT STANDARD
Density	≥ 670 kg/m <sup>3</sup>	EN13986
Reaction to fire	D-s2, d0	
Thickness	10 mm +/- 0,3 mm	
Formaldehyde Emission Class	E1	

## INSTALLATION, EXECUTION, TRANSPORT AND STORAGE

The package typically contains two panels. The panels should be acclimated to the expected usage environment before installing to ensure best end result. Vito Lacquered Veneer must be stored horizontally and on a flat surface, in a dry place, with the plastic packaging still on.

Before installation, inspect the panels for any damage, such as water exposure, dents, or other defects. If you notice any visible damage, do not install the panels, and contact your dealer for guidance.

For detailed instructions on installation, please see installation manual.

**CLEANING**

Vito Lacquered Veneer is a natural product with a thin layer of lacquered oak or birch surface. Normal maintenance is with dry lint-free cloth to remove dust.

For removal of stains, you may use a damp, lint-free cloth with small amount of soap and water. Use of mild detergents with pH-range 7-9 is recommended. Scrubbing agents is not recommended as this will affect the lacquered layer.

**WASTE MANAGEMENT**

100 % recyclable wooden waste

**TYPE OF PACKAGING**

Environmental plastic

**HSE REFERENCES**

Vito Lacquered Veneer meets the requirements for emission levels and does not contain any known hazardous, flammable, or allergenic substances. The wall system does not pose any health risk during installation or normal use.

**WARRANTY**

All our panels come with a 15-year product warranty, and a lifetime expectancy which well exceeds the warranty period. The expected lifetime of product is under normal conditions same as the building lifetime, or minimum 30 years.

**SUPPLIER: FIBO AS**

Address: Industriveien 2, 4580 Lyngdal, Norway

Phone: +47 38 13 71 00

Website: <http://www.fibosystem.com>

E-mail: [info@fibosystem.com](mailto:info@fibosystem.com)

Contact person: **Head of Product**

**APPROVALS**

PEFC certification: PBN-PEFC-COC-064510

FSC certification: NC-COC-064510

**REFERENCES**

Harmonized Standard EN 13986