

Declaration of Performance 120005-EN Fibo Seal

- 1. Unique identification: Fibo Seal (multiple colours)
- 2. Construction product id: See product packaging
- 3. Intended use: Sealant for bathrooms with Fibo Wallpanel
- 4. Producer name and address: Fibo AS, Industriveien 2, 4580 Lyngdal, Norge
- 5. System and verification of consistency of the contruction product (Annex V): System 3
- 6. System concerning a harmonised standard for construction product:

 The notified body Tecnalia (1292) performed tests and issued a test report
- 7. Declared performance: Metode A, Substrate: **Aluminium (without primer)**

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONIZED SPECIFIKATION
Reaction to fire	Е	
Release of chemicals dangerous to health and environment	NPD: See Safety Datasheet	
Water and air tightness		
a) Resistance to flow	≤ 5 mm	EN 15651-3:2012
b) Loss of volume *	≤ 55 %	
c) Durability	Approved	
d) Microbiel growth	0	

 $^{^{\}star}$ According to classification. Actual loss of volume under 2%

Signed on behalf of the manufacturer.

Lyngdal, 30.09.2024

Erland Pettersen, Product Manager Fibo AS, Industriveien 2, 4580 Lyngdal

SILL (AL

www.fibosystem.com