

Management, Operations and Maintenance (MOM) Vito Poplar Plywood

FORMAT

TABLE 1: PRODUCT DIMENSIONS

PRODUCT	DIMENSION
Vito Poplar Plywood	2400 mm x 600 mm x 9 mm

PRODUCT DESCRIPTION

Vito Poplar Plywood consists of 5 layers of high-quality poplar veneer with an invisible click lock system for hidden fastening to backwall to provide a smooth and naturally beautiful look.

INTENDED USE

Vito Poplar Plywood is a high-quality construction material for indoor use, in dry areas. It is ideal for walls where a seamless expression of natural wooding is required. The panels have a hidden fastening system with a special click lock patent, which makes it easy to install and gives a flawless appearance.

Vito Poplar Plywood is a 9 mm thick panel delivered in a standard-length of 2400 mm by 600 mm width. The panels are installed with screws towards preferred backwall solution. We recommend use of Fibo Screw (article nr 810006/810007/810011) to maintain a guaranteed fit in the invisible lock-system.

TABLE 2: RELEVANT PROPERTIES

PROPERTIES	PERFORMANCE	HARMONIZED PRODUCT STANDARD
Density	$\geq 400 \text{ kg/m}^3$	EN13986
Reaction to fire	D-s2, d0	
Thickness	9 mm +/- 0,3 mm	
Screw extraction	$\geq 840 \text{ N}$	
Formaldehyde Emission Class	E1	

INSTALLATION, EXECUTION, TRANSPORT AND STORAGE

The package typically contains two panels. The panels should be acclimated to the expected usage environment before installing to ensure best end result. Vito Poplar Plywood must be stored horizontally and on a flat surface, in a dry place, with the plastic packaging still on.

Before installation, inspect the panels for any damage, such as water exposure, dents, or other defects. If you notice any visible damage, do not install the panels, and contact your dealer for guidance.

For detailed instructions on installation, please see installation manual.

CLEANING

Vito Poplar Plywood is a natural product with a honed surface. You may clean the surface with water and soap to remove difficult stains. Otherwise, the panels can be vacuum cleaned or brushed with a lint-free cloth.



WASTE MANAGEMENT

Code for waste management
100 % recyclable wooden waste

TYPE OF PACKAGING

Environmental plastic

HSE REFERENCES

Vito Poplar Plywood meets the requirements for emission levels and does not contain any known hazardous, flammable, or allergenic substances. The wall system does not pose any health risk during installation or normal use.

EXPEVTED LIFETIME

The expected lifetime of product is under normal conditions same as the building lifetime, or minimum 30 years.

SUPPLIER: FIBO AS

Address: Industriveien 2, 4580 Lyngdal, Norway

Phone: +47 38 13 71 00

Website: <http://www.fibosystem.com>

E-mail: info@fibosystem.com

Contact person: **Head of Product**

APPROVALS

PEFC certification: PBN-PEFC-COC-064510

FSC certification: NC-COC-064510

REFERENCES

Harmonized Standard EN 13986