

Produkt: Shower Wall	
Standard size: 1220x240mm with Aqualock	
Area for usage: Bathroom and shower walls in dry and wet rooms	
Fitting	Panels can be fitted directly onto a concrete wall, over tiles or, if necessary, onto a timber framework. Refer to fitting instructions.
Fixture	corrosion free screw and vinyl covered fixture
SUPPLIER	
Name	Fibo AS
Adress	Industri veien 2, 4580 Lyngdal, Norway
Phone / Fax	+47 38 13 71 00 / +47 38 13 70 51
WEB adr	http://www.fibosystem.com
Mail	ordre@fibosystem.com
Contact	Elise Almås, Product manager

PRODUCT DESCRIPTION	
Construction	The Respatex panels consist of a wooden core material covered with a decorative high-pressure laminate (HPL) on the front face and a backing laminate (HPL) on the reverse side. The long edges are delivered with a tongue and groove system for concealed fixing with a 45 degree chamfered short edge on one end.
Brilliance Test Method according to ISO-2813	(Reference point: 60 Degrees) High gloss (HG) 120 Degrees (of brilliance) Gloss (G) 70 -80 Degrees (of brilliance) Silk (S) 10-18 Degrees (of brilliance)
Finishes	Product finishes for individual colours are available as indicated on the three Colour Collection pages: Silk S, Gloss G, High Gloss HG
Characteristics test method according to EN 438-1 and 2	Impact Resistance Good, Wear Resistance (IP) Good Scratch resistance > 350, Heat resistance Good Water absorption Good Swelling < 3%, Dimensional stability < 3% Lengthwise < 3%, Crosswise < 3%, Light resistance 6-8
The core	This is a specially developed 7-layer plywood consisting of birch. The Ply core is excellent for shower rooms and other rooms with extremely high humidity
Ply core	Paper forms the basis of high-pressure laminates (HPL). The paper is impregnated with phenolic and melamine resins, dried and finally compressed to form an extremely hard and stable material - High-pressure laminate HPL.
Cleaning/maintenance	Household solvents, disinfectants and detergents do not affect the durable surface. Abrasive cleaners should not be used.
High-pressure laminate	The High pressure Laminate is a surface material to be bonded to different kinds of substrates. High Pressure Laminates have a very good wear resistance as well as resistance to most chemicals.
Stock	Respatex has a warehouse in Grimsby, North Lincolnshire and Edinburgh Scotland. If an item is in stock then delivery time is approximately 5 to 7 working days from time of order

REMARK	
Storage	Panels should be stored flat under cover. The decorative surfaces should be facing each other.
Asthma/Allergy	Approved 28/10.00 by Norges Astma- og Allergiforbund.
Approvals:	EN.438-norm, VTT, NAAF, SITAC

Changed: 09.12.2016

Replaces: 22.06.2015